

Cod: 11605

3-door pizza counter 202x80x100h cm for pizzeria-restaurant complete with display case for 9 GN 1/3 trays



Description

Pizza counter complete with stainless steel ventilated refrigerated display case for 9 GN 1/3 trays with 3 doors size 2020x800x1000h mm for pizzeria restaurant. The product has a rounded corner on the bottom for easy cleaning and is equipped with wheels. Self-closing doors. The built-in unit is removable for easy maintenance. The operating temperature is in the range of -2° C/ + 8° C and can be easily adjusted by means of an electric controller with temperature display. The counter is equipped with a door fitted with a heating element for the elimination of condensation and an easily removable magnetic seal. The cabinet measures 2000x395x435h mm and is made of high quality stainless steel to guarantee a high level of reliability, performance, style and excellent value for money. Stainless steel interior and exterior. Electronic controller with temperature display that has a temperature range of +2 +8 °C.

Trays and lids are available as options.

In basso la scheda tecnica di ogni prodotto del Kit:

SKU: 92690031675

Pizza counter 3 doors 2020x800x1000h mm for pizzeria restaurant - FC

Dimensions

Dimensioni esterne	2020x800x1000 mm
Dimensioni imballo	2055x830x1180 mm
Dimensioni interne	1562x630x580 mm

Technical data

Alimentazione	Electric
Capacità	580 Lt
Classe energetica	C
Frequenza	50 Hz
Gas refrigerante	R600A
Materiale	stainless steel
Peso lordo	326 kg
Peso netto	306 kg
Potenza Elettrica	0.398 kW
Refrigerazione	ventilated
Sbrinamento	electric defrost
Temperatura ambiente massima	35 °C
Temperatura d'esercizio	-2 +8 °C
Termostato	electrical
Voltaggio	230 V

Standard equipment

In dotazione	7 coppie guide per porta
--------------	--------------------------

SKU: 95591336006001

GN 1/3 2000x395x435h mm +2 +8 °C refrigerated display case for pizza toppings, pizza crusts with energy-saving right-hand motor

Dimensions

--	--

Dimensioni esterne

2000x395x435 mm

Technical data

Alimentazione	Electric
Capacità vaschette	9 GN 1/3
Frequenza	50 Hz
Gas refrigerante	R600A
Refrigerazione	static
Temperatura ambiente massima	32 °C
Temperatura d'esercizio	+2 +8 °C
Termostato	dixell
Voltaggio	230 V