

Cod: 11606

2-door 151x80x100h cm pizza counter for pizzeria-restaurant complete with display case for 7 GN 1/4 trays



Description

Pizza counter complete with stainless steel ventilated refrigerated display case for 7 GN 1/4 trays with 2 doors size 1510x800x1000h mm for pizzeria restaurant. The product has a rounded corner on the bottom for easy cleaning and is equipped with wheels. Self-closing doors. The built-in unit is removable for easy maintenance. The operating temperature is in the range of -2° C/ + 8° C and can be easily adjusted by means of an electric controller with temperature display. The counter is equipped with a door fitted with a heating element for the elimination of condensation and an easily removable magnetic seal. The 1500x335x435 mm display case is made of high quality stainless steel to guarantee a high level of reliability, performance, style and excellent value for money. Stainless steel interior and exterior. Electronic controller with temperature display that has a temperature range of +2 +8 °C.

Trays and lids are available as options.

In basso la scheda tecnica di ogni prodotto del Kit:

SKU: 92690021610

Pizza counter 2 doors 1510x800x1000h mm for pizzeria restaurant - FC

Dimensions

Dimensioni esterne	1510x800x1000 mm
Dimensioni imballo	1510x830x1180 mm
Dimensioni interne	1052x630x580 mm

Technical data

Alimentazione	Electric
Capacità	390 Lt
Classe energetica	C
Frequenza	50 Hz
Gas refrigerante	R600A
Materiale	stainless steel
Peso lordo	267 kg
Peso netto	252 kg
Potenza Elettrica	0.275 kW
Refrigerazione	ventilated
Sbrinamento	electric defrost
Temperatura ambiente massima	35 °C
Temperatura d'esercizio	-2 +8 °C
Termostato	electrical
Voltaggio	230 V

Standard equipment

In dotazione	7 coppie guide per porta
--------------	--------------------------

SKU: 88260237006001

Refrigerated display case for condiments, pizza crusts GN 1/4 1500x335x435h mm +2 +8 °C with energy-saving right-hand motor

Dimensions

--	--

Dimensioni esterne	1500x335x435 mm
--------------------	-----------------

Technical data

Alimentazione	Electric
Capacità vaschette	7 GN 1/4
Frequenza	50 Hz
Gas refrigerante	R600A
Refrigerazione	static
Temperatura ambiente massima	32 °C
Temperatura d'esercizio	+2 +8 °C
Termostato	dixell
Voltaggio	230 V