

Cod: 518

Electromechanical hood dishwasher, square basket 500x500 mm height 430 mm



Description

The Ristoattrezzature line of hood dishwashers is designed to offer excellent washing results, meeting the requirements of ease of use, low running costs and long life. Thanks to the capot dishwashers, perfectly clean dishes are always achieved with constant and powerful rinsing. The rinse boiler offers a unique rinse temperature maintenance system to guarantee the best results. Impellers and rinsing jets, together with powerful and exclusive pumps, perform a high-performance action, so that perfectly clean dishes are achieved at all times. The control panel is user-friendly, making the user's tasks easier. Special Incoloy heating elements, exceptional for their rapid heating qualities, offer a significant reduction in electricity consumption. Our hood dishwashers made of AISI 304 18/10 stainless steel are manufactured in strict compliance with the environment and current regulations. The hood dishwasher has a passage of 43 cm and is suitable for washing pizza plates. It can hold up to 6 GN1/1 baking tins: to be able to wash GN1/1 baking tins, it is necessary to purchase the GN1/1 baking tin basket. The dishwasher is not equipped with a detergent dispenser and it is not possible to request one. Attention: if the height of the drain in the wall is higher than 56 cm from flush with the floor, a drain pump must be purchased together with the machine. Please contact the sales department for more information.

Supplied with N°1 500x500 mm basket, N°1 Rinse aid dispenser and N°1 Double tank filter.

Dimensions

Altezza utile	430 mm
Dimensioni cesto	500x500 mm
Dimensioni esterne	695x760x1460 mm

Technical data

Acqua alimentazione	50 °C
Alimentazione	Electric
Capacità	55 Lt
Capacità boiler	9 Lt
Capacità pompa	420 Lt/h
Frequenza	50 Hz
Peso	105 kg
Potenza Elettrica	6.75 kW
Potenza pompa	0.75 kW
Pressione	2 - 4 bar
Resistenza boiler	6 kW
Resistenza vasca	4.5 kW
Rumorosità	62 db
Temperatura lavaggio	85 °C
Temperatura risciacquo	55 °C
Tempo ciclo	180 "
Voltaggio	230 V, 400 V

Standard equipment

In dotazione	N°1 cesto 500x500 mm, N°1 Dosatore brillantante e N°1 Doppio filtro vasca.
--------------	--